Waste/recycle sets

Premium TANDEM and TANDEMBOX solutions for waste/recycle cabinets

Waste/recycle
solutions for every kitchen

Blum's new TANDEM and TANDEMBOX waste/recycle sets are the premium solutions for waste/recycle cabinets in the kitchen. They feature BLUMOTION soft closing and TANDEM smooth running action.

With the SERVO-DRIVE touch-to-open feature, drawers open automatically with just a touch of the drawer front or a light pull of the handle. Customers will be amazed by the quality and ease of use.

Other applications

Interior roll-out

Bottom mount

TANDEMBOX waste/recycle set with SERVO-DRIVE

Application

Description

- Pre-assembled bottom mount solution
- TANDEMBOX heavy duty full extension drawer system
- For 12", 15" and 18" minimum opening widths
- For face frame and panel applications
- Three-dimensional drawer front adjustment
- Maximum **6** (1/4") cabinet bottom recess
- TANDEM smooth running action
- 175 lb static, 150 lb dynamic load rating
- SERVO-DRIVE touch-to-open feature

Basic components



NOTE: Bins not included

Components

TANDEMBOX waste/recycle set

SERVO-DRIVE inside

BLUMOTION inside



Set includes:

1. TANDEMBOX heavy duty runner set with pre-mounted #6 x 1" wood screws for installation (qty 8)
2. Pre-assembled silk white TANDEMBOX drawer

- Installation template and instructions
- #6 x 5/8" wood screws for attachment to drawer front (qty 10)
- TANDEMBOX cover caps (qty 2)

TANDEMBOX waste/recycle set	Drawer length	Part no.
For 12" minimum opening width	**550** (21-5/8")	**356M55B7SAB**
For 15" minimum opening width	**550** (21-5/8")	**356M55B7SAD**
For 18" minimum opening width	**550** (21-5/8")	**356M55B7SAF**

SERVO-DRIVE waste/recycle set



Set includes:

1. Drive unit (pre-attached)
2. Double bottom bracket with #6 x 1" wood screws (qty 2)
3. Adapter plate
4. 110 volt plug-in power supply with six feet of universal cable
5. Screw-on distance bumpers (qty 4) with #6 x 5/8" wood screws for installation (qty 8)
6. INSERTA cable connector
7. Cable end protectors (qty 2)
8. Cable clips (qty 4)

- Installation template, instructions and user manual

SERVO-DRIVE waste/recycle set	Part no.
	Z10NA20UGUS

NOTE: Power supply will operate up to two drive units in a double bottom bracket application (second drive unit sold separately)

© 2013 Blum, Inc. Subject to technical modifications without notice

Specifications

Drawer and cabinet specifications

Front view


opening width
6 (1/4") minimum top clearance
maximum height with bin = opening height minus 22 (7/8")
opening height
16 (5/8")
16 (5/8") maximum bottom clearance depending on cabinet bottom recess

A retainer or wood block should be added to the TANDEMBOX drawer to secure the bins and keep them from pressing against the drawer front during daily operation

NOTE: Minimum opening height = **233** (9-3/16")

Important

Bin width and height must be considered when designing your cabinet (see the diagram on the left).

Minimum inside cabinet depth	
With SERVO-DRIVE	**574** (22-19/32")
Without SERVO-DRIVE	**569** (22-13/32")

Drawer front attachment



	Cabinet bottom recess		
	6 (1/4")	**3** (1/8")	Flush
Y	**16** (5/8")	**19** (3/4")	**22** (7/8")

Waste/recycle set	356M55B7SAB	356M55B7SAD	356M55B7SAF
X	**154.5** (6-3/32")	**192.5** (7-19/32")	**230.5** (9-1/16")
Z	**146.5** (5-25/32")	**184.5** (7-1/4")	**222.5** (8-3/4")
minimum opening width	**305** (12")	**381** (15")	**457** (18")

Set mounting specifications

Top view



NOTE: Orange dots indicate pre-mounted screw locations. All four screws are required to meet specified load capacities.

© 2013 Blum, Inc.

TANDEM waste/recycle set with SERVO-DRIVE

Application

Description

- Pre-assembled bottom mount set
- TANDEM plus BLUMOTION heavy duty full extension concealed drawer runners
- For 12", 15" and 18" minimum opening widths
- For face frame and panel applications
- Tool-free height and tilt adjustment
- Maximum **6** (1/4") cabinet bottom recess
- 125 lb static, 110 lb dynamic load rating
- SERVO-DRIVE touch-to-open feature

Basic components



NOTE: Drawer and bins not included

Components

TANDEM waste/recycle set

SERVO-DRIVE inside

BLUMOTION inside



Set includes:

1. TANDEM plus BLUMOTION heavy duty runner set with pre-mounted #6 x 1" wood screws for installation (qty 8)
2. Standard locking device (qty 2) with #6 x 5/8" wood screws for installation (qty 4)
- Installation template and instructions

TANDEM waste/recycle set	Drawer length	Part no.
For 12" minimum opening width	**533** (21")	**569R5337BB**
For 15" minimum opening width	**533** (21")	**569R5337BD**
For 18" minimum opening width	**533** (21")	**569R5337BF**

SERVO-DRIVE waste/recycle set



Set includes:

1. Drive unit (pre-attached)
2. Double bottom bracket with #6 x 1" wood screws (qty 2)
3. Adapter plate
4. 110 volt plug-in power supply with six feet of universal cable
5. Screw-on distance bumpers (qty 4) with #6 x 5/8" wood screws for installation (qty 8)
6. INSERTA cable connector
7. Cable end protectors (qty 2)
8. Cable clips (qty 4)
- Installation template, instructions and user manual

SERVO-DRIVE waste/recycle set	Part no.
	Z10NA20UGUS

NOTE: Power supply will operate up to two drive units in a double bottom bracket application (second drive unit sold separately)

© 2013 Blum, Inc. Subject to technical modifications without notice

Specifications

Drawer and cabinet specifications

Front view


opening width
6 (1/4") minimum top clearance
outside drawer width
inside drawer width
maximum height with bin = opening height minus 27 (1-1/16")
opening height
21 (13/16")
13 (1/2")
21 (13/16") maximum bottom clearance depending on cabinet bottom recess

NOTE: Drawer side material thickness may vary. Precise measurement of drawer side material thickness should be used when calculating outside drawer width using the table below. Inside drawer width **must** equal opening width minus **42** for TANDEM to align and function optimally.

Important

Bin width and height must be considered when designing your cabinet (see the diagram on the left).

Minimum inside cabinet depth	
With SERVO-DRIVE	**577** (22-23/32")
Without SERVO-DRIVE	**557** (21-15/16")

Drawer back preparation



Waste/recycle set	Minimum opening width	Inside drawer width	For drawer side thickness				
			16 (5/8")	**15** (19/32")	**14** (9/16")	**13** (1/2")	**12** (15/32")
569R5337BB	**305** (12")	**263** (10-11/32")	**295** (11-5/8")	**293** (11-17/32")	**291** (11-15/32")	**289** (11-3/8")	**287** (11-5/16")
569R5337BD	**381** (15")	**339** (13-11/32")	**371** (14-19/32")	**369** (14-17/32")	**367** (14-7/16")	**365** (14-3/8")	**363** (14-9/32")
569R5337BF	**457** (18")	**415** (16-11/32")	**447** (17-19/32")	**445** (17-17/32")	**443** (17-7/16")	**441** (17-3/8")	**439** (17-9/32")
NOTE: Drawer length is **533** (21") for all sets			Outside drawer width				

Set mounting specifications

Top view



Waste/recycle set	Z
569R5337BB	**141.5** (5-9/16")
569R5337BD	**179.5** (7-1/16")
569R5337BF	**217.5** (8-9/16")

NOTE: Orange dots indicate pre-mounted screw locations. All four are required to meet specified load capacities.

© 2013 Blum, Inc.

TANDEM plus BLUMOTION 569R – heavy duty bottom mount runners

Application

Description

- Full extension bottom mount concealed drawer runners with BLUMOTION
- For face frame and panel applications
- Tool-free height and tilt adjustment
- Concealed roller carriages with permanently lubricated synthetic rollers create a smooth running action
- Locking devices enable easy drawer insertion and removal
- 125 lb static, 110 lb dynamic load capacity
- **Available Spring 2014**

Basic components



Applications

Bottom mount drawer


Interior roll-out

Roll-out shelf

Components

TANDEM plus BLUMOTION bottom mount runner set

One set required per drawer

BLUMOTION inside



Set includes:

1 TANDEM plus BLUMOTION heavy duty runner set with #6 x 5/8" wood screws for installation (qty 10)

2 Standard locking device (qty 2) with #6 x 5/8" wood screws for installation (qty 4)

- Installation instructions

Interior roll-outs and roll-out shelf applications must be mounted to the bottom of the cabinet or to a fixed shelf/pane

Overall cabinet depth	Drawer length	TANDEM plus BLUMOTION set
610 (24")	**533** (21")	**569R5330B**

NOTE: These runners are for **16** (5/8") maximum drawer side thickness

NOTE: Rear brackets and sockets cannot be used. Cabinet bottom must be flush with top surface of bottom rail unless bottom mount spacers are used.

Bottom mount spacer

Used to install bottom mount 569R runners in cabinets with a bottom recess of up to **6** (1/4")

	Part no.
Bottom mount spacer	**T59.T570**
Wood screw for installation	**606W**

© 2013 Blum, Inc. Subject to technical modifications without notice

Specifications

Drawer and cabinet specifications

Drawer box specifications

Front view



NOTE: Drawer side material thickness may vary. Precise measurement of drawer side material thickness should be used when calculating outside drawer width using the table below. Inside drawer width **must** equal opening width minus **42** for TANDEM to align and function optimally.

Calculating outside drawer width					
For drawer side thickness	**16** (5/8")	**15** (19/32")	**14** (9/16")	**13** (1/2")	**12** (15/32")
Deduct from opening width	**10** (13/32")	**12** (15/32")	**14** (9/16")	**16** (5/8")	**18** (23/32")

Example: For 21" opening width and a 5/8" thick drawer, 21" minus 3/8" = 20-5/8" drawer width

Drawer back preparation

Rear view



Runner comparison

Side view

569R – No vertical profile

569H – Vertical profile

Runner mounting specifications

Top view



NOTE: Orange dots indicate screw locations required to meet specified load capacities (minimum 4 screws)

© 2013 Blum, Inc.

TANDEMBOX adjustments

Bin configurations

15" wide cabinet – one bin



18" wide cabinet – two bins



21" wide cabinet – two bins



NOTE: Accommodates a wide range of standard bin sizes

Drawer adjustment

Height adjustment



Use a Phillips screwdriver to adjust drawer front up or down as shown (±2 mm). Repeat on left side if necessary.

Side adjustment



Use a Phillips screwdriver to adjust drawer front left or right (±2 mm). Adjust left or right side equally by turning both toward or away from drawer front.

Tilt adjustment



Slide gallery cover towards drawer back. Rotate orange adjustment piece as shown and slide cover back towards drawer front. Repeat on left side if necessary.

Drawer insertion and removal

Insertion





Removal



© 2013 Blum, Inc. Subject to technical modifications without notice

Cross rail adjustment

1 Slide to desired position



2 Lock cross rail into place



Cross rail removal

1 Unlock cross rail



2 Lift cross rail to remove



 © 2013 Blum, Inc.

TANDEM adjustments

a

Bin configurations

15" wide cabinet – one bin



18" wide cabinet – two bins



21" wide cabinet – two bins



NOTE: Accommodates a wide range of standard bin sizes. Detailed drawings of recommended drawer box specifications available at blum.com.

Drawer adjustment

Height adjustment

1 Press up on adjustment tab
2 Push towards back of drawer



Maximum **3** (1/8") rise of drawer front (tool-free)

Tilt adjustment

Rotate the tilt adjustment lever on the rear of each runner to lift the back of the drawer and tilt the top of the drawer front forward.



Maximum **5** (3/16") rise of drawer back (tool-free)

NOTE: Height and tilt adjustments available with all combinations of locking devices and runners

Drawer insertion and removal

Drawer insertion

Extend the drawer runners fully. Place the drawer on the runners and close. The locking devices automatically engage with the runners. Make adjustments if necessary.



Drawer removal

1 Squeeze orange handles on locking devices
2 Pull drawer straight out and up



© 2013 Blum, Inc. Subject to technical modifications without notice

Notes

 © 2013 Blum, Inc.

Blum, Inc. Headquarters, Stanley, NC

Why choose Blum

Blum, Inc. is a leading manufacturer of functional hardware for the kitchen cabinet and commercial casework industries specializing in lift systems, concealed hinges and drawer runner systems. Virtually all of the hardware needed to assemble and make cabinets functional is available within the wide range of quality Blum products. Blum supports the U.S. market with a network of more than 150 dependable distributors, 40+ knowledgeable Blum sales representatives and an experienced customer service department.

Commitment to manufacturing in the U.S.

Blum manufactures many of its products in our 450,000 sq ft manufacturing, logistics and warehouse facility located in Stanley, North Carolina. Manufacturing closer to the customer allows Blum to react quickly to changing customer needs including unexpected surges in demand. Customer pickups and deliveries can be timed to better match their production schedules. Blum is committed to manufacturing in the U.S. for the U.S. market.

Product development at Blum considers all of the various customers who will come in contact with our products. With this “Global Customer Benefits” philosophy we strive to create advantages for all users.

ISO 9001
Certified Quality System

Blum, Inc. is ISO 9001 certified which means that you are assured of consistent quality in every Blum product. What’s more they exceed the requirements of ANSI/ BHMA standards for cycle life, static load and self-closing performance.

Please visit blum.com for information on other Blum products
LIT.WRS1100.11.13 © 2013 Blum, Inc.

Blum, Inc.
7733 Old Plank Rd.
Stanley, NC 28164
800-438-6788
blum.com

ISO 9001
Certified Quality System

blum®